

A new generation of pagers for today's professional.

# BRAVO



## **BRAVO 501 POCSAG** Numeric Pager

### **Features: POCSAG**

- Up to 12 Alerts
- 4 cap code capacity (any frame)
- Low cell alert
- Battery gauge
- Programmable power-Up screen
- Stores up to 20 personal messages
- Message time stamping
- Shows time and date
- Built-in alarm clock
- Reminder alert
- Delete individual messages or erase all
- Backlight Display
- UL Class I Division II, Groups A, B, C, D

### **Specifications: VHF/UHF/900 POCSAG**

Model Number .....	154-VPA, B, C, D, E (VHF)
.....	154-UPA, B, C, D (UHF)
.....	154-9P (900MHz)
Frequency .....	VHF Synth. (135 - 174MHz)
.....	UHF Synth. (452 - 468MHz)
.....	900MHz Crystal (929 - 932MHz)
Code Format .....	POCSAG, 512/1200/2400 bps
Channel Spacing .....	25 kHz
Frequency deviation .....	+/- 4.5 kHz
Paging Sensitivity.....	5 mV/m for 512 bps
.....	7 mV/m for 1200 bps
.....	9 mV/m for 2400 bps
EIA Selectivity .....	55 dB
EIA Spurious and Image .....	50 dB
IM Rejection .....	50 dB
Operating Temp .....	-10°C to 50°C
Alert Tone Loudness.....	75 dB @ 12 inches
Battery Type .....	1 x Alkaline AAA
Battery Life .....	~35 days for 1200bps
.....	2 pages a day
Weight (with battery).....	45 grams
Size .....	.63 x .43 x 17.6 mm



**BRAVO 501** 